

IP65 Fire Rated LED Downlight


- ★ Cost effective
- ★ 50,000 hours lifespan with 5 years warranty
- ★ BS476-21 Fire rated Integrated Downlight
- ★ Facial Bezel Interchangeable
- ★ IP65 Water-proof
- ★ Trailing Edge Dimmable
- ★ Different bezel colours options (brushed steel,chrome,brass, black)



Part Code:GIA-FR65

General Specification					
Product Dimension	Φ 80*H51mm			Cut-out Size	55-70mm
Finish/Color	White/black			Packing Method	Color box
IP Rating	IP65 Fascia			Energy Rating	A++
Dimmable (Yes/No)	Yes			Warranty	5years
Light Source Specification				Electrical Specification	
CCT (K)	3000K	4000K	6000K	Input Voltage	200-240V AC 50Hz
Lumens Per Watt	103	113	108	Input Current	0.1A
Lumen output	620	680	650	Input Power	6W
CRI (Ra)	80			Power Factor	>0.85
Lifetime	35000hrs			Elec. Classification	Class I
Beam Angle	60°			Control Gear Spec	Constant current
Type of LED	6*1W SMD				
Packing Specification					
Box Dimensions	100*90*73mm			Carton Dimensions	43X39X25cm
QTY/CTN	48			G/N Weight	11kg
Installation					
Distance to Other Obj.	50mm void space			Ambient Temp	-10 °C ~ 40 °C
Fixing Method	Spring clips				


★ Available in the these colours upon request.




Brushed steel



Chrome



Brass



Black